

The SS500 Series[™] is exclusively available through Trench Drain Systems. This shallow stainless steel drainage system is specifically designed for small commercial markets. The 6.25" (OD) 16 gauge stainless steel channels feature a built-in 0.5% slope. Stainless U-shaped channels come in 48" and 96" lengths with neutral channels to allow for longer runs. Custom sections are available.

- Up to 56' of continuous slope at .5%
- 4' & 8' channel sections
- Neutral and half channels
- Transition channel (from SS500 - SS600)
- Tee sections and 90° elbows
- 20+ grating options
- Lightweight for rapid installation
- 304 Stainless steel
- 316 Stainless available (special order)
- Utilizes standard grating
- Single concrete pour placement
- Neoprene Gaskets
- Hardware included



SS500 Series Depth Chart

Channel #	Inlet Depth	Outlet Depth
500N*	2.0	2.0
500NB*	2.0	2.0
501	2.0	2.5
501B*	2.0	2.5
501H*	2.5	2.5
501HB*	2.5	2.5
501N*	2.5	2.5
501NB*	2.5	2.5
502	2.5	3.0
502B*	2.5	3.0
502H*	3.0	3.0
502HB*	3.0	3.0
502N*	3.0	3.0
502NB*	3.0	3.5
503	3.0	3.5
503B*	3.0	3.5
503H*	3.5	3.5
503BH*	3.5	3.5
503N*	3.5	3.5
503NB*	3.5	3.5
504	3.5	4.0
504B*	3.5	4.0
504H*	4.0	4.0
504BH*	4.0	4.0
504N*	4.0	4.0
504NB*	4.0	4.0
505	4.0	4.5
505B*	4.0	4.5
505H*	4.5	4.5
505BH*	4.5	4.5
505N*	4.5	4.5
505NB*	4.5	4.5
506	4.5	5.0
506B*	4.5	5.0
506H*	5.0	5.0
506BH*	5.0	5.0
506N*	5.0	5.0
506NB*	5.0	5.0

*N = Non-sloped
*H = Half (Non-sloped 48")
*B = Bottom Outlet