




Declaration of Performance

1. No:	PF04 - 0101
2. Product:	ULMA D100, DP100, DPS100, SU100, SU200 and M100V
3. Intended use:	Type M drainage channel for the collection and disposal of surface water in areas for pedestrians and vehicular traffic.
4. Manufacturer:	ULMA Architectural Solutions Barrio Zubillaga, 89 Apdo.20 – 20560 Oñati Gipuzkoa – SPAIN
5. Authorised representative:	---
6. Assessment and verification system:	System 3
7. Notified Body:	No. 0370 LGAI TECHNOLOGICAL CENTER, S. A./Applus Campus de la U.A.B. Apartado,18. (08193) BARCELONA.
8. Type Test Ref.:	Various. Available under requirement.
9. Essential Characteristics:	Water tightness – jointing of drainage channels: No leakage Load bearing capacity, deflection under load: - Maximun load: C250 - Permanent set: NPD Durability: - Flexural strength ≥ 22 N/mm² - Compressive strength ≥ 90 N/mm²
10. Harmonized Standard:	EN 1433:2002
11. Specific Technical Documentation:	---

The performance of product identified in point 2 is in conformity with the declared performance in point 9.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Mikel Izurieta
Director General
ULMA Architectural Solutions

Oñati, July 2013