

### **Z884 Applications**

**Sidewalks** 

**Parking Garages** 


**Gas Stations** 

**Kitchens** 

**Pools** 

Residential

# **Installation Specification**



3-1/4" Throat / 4-3/4" Overall Width

#### Features and Benefits


- 40" Modular Channel Sections with 20" Grates
- Smooth Seamless Construction Clean, sanitary installation.
- Durable and Lightweight Strong corrosion-resistant material.
- 2-7/8" Trench Depth For depth restricted applications.
- Variety of Gratings Able to meet specific job requirements.
- Grate Options Available in ADA.
- -CG Cast Iron Grate
- -FG Fabricated Galvanized Steel Slotted Grate
- -FS Fabricated Stainless Steel Slotted Grate
- -HPP Heel-proof Polyethylene Grate
- -PG Perforated Galvanized Steel Grate
- -PS Perforated Stainless Steel Grate


	Z884 I	Dimensional Da	ata	
	Overall Depth		Approx. Wt. (Less Grate)	
Number	Inches	mm	Lbs.	Kg
884	2.875	73	2.3	1.04

**Engineering Specification** Channels shall be 40" long, 4-3/4" wide, and have a 3-1/4" wide throat. Modular channel sections shall be made of High Density Polyethylene (HDPE), have interlocking ends, and radiused bottom. Channel shall be provided flat (neutral) with a 2.875" invert. Channels shall have clips molded into the sides of the channel to accommodate vertical rebar for positioning and anchoring purposes. Choice of class A, B, and C grates shall be available with H-20 and/or ADA compliance with mechanical lockdown devices. End caps and catch basins shall be available to complement the channels and grates. End outlets in 2" diameter and bottom outlets in 3" diameter shall be available. Trench drain shall be Flo-Thru model Z884.



# **Z884** 4 1/8" WIDE GRATES







Please Check	
	1

BZ- Bronze Decorative			
Material : Bro	nze		
DIN Rating : 0	DIN Rating: Class A		
Weight: 4.05 # per ft.			
Open Area: 11.62 sq. in. per ft.			
ANSI Rating: Light Duty			
Application: Decorative Heelproof			
Slot Width/Hole Size: 0.25"			
ADA	H-20	FAA	
Yes	No	No	

Please	Item
Check	No.
	2

FG- Fabricated Galvanized Steel Slotted			
Material : Galvanized Steel			
DIN Rating: Class A			
Weight: 2.79 # per ft.			
Open Area: 7.8 sq. in. per ft.			
ANSI Rating: Light Duty			
Application: Lt. Vehicle Traffic			
Slot Width/Hole Size: 0.375"			
ADA	H-20	FAA	
No	No	No	





Please Check	
	3

FS- Fabricated Stainless Steel Slotted		
Material : Stain	less Steel	
DIN Rating : Class A		
Weight: 2.88 # per ft.		
Open Area: 7.8 sq. in. per ft.		
ANSI Rating: Light Duty		
Application: Lt. Vehicle Traffic, Food/Bev. Process		
Slot Width/Hole Size: 0.375"		
ADA	H-20	FAA
No	No	No

Please	Item
Check	No.
	4

HPP- Heelproof Slotted			
Material : HDPE			
DIN Rating : Class A			
Weight: .69 # per ft.			
Open Area: 10.78 sq. in. per ft.			
ANSI Rating: Light Duty			
Application: Pedestrian, Chem., Swimming Pool			
Slot Width/Hole Size: 0.25"			
ADA	H-20	FAA	
Yes	No	No	

**Form #** FT965

**Date:** 9/5/07


**C.N. No.** 109480


Rev. ORIG

Page 1 of 2



### **Z884** 4 1/8" WIDE GRATES






Please Check	Item No.	
	5	

PG- Perforated Galvanized Steel			
Material : Gal	vanized Stee	el	
DIN Rating: Class A			
Weight: 2.67 # per ft.			
Open Area: 15.25 sq. in. per ft.			
ANSI Rating: Light Duty			
Application: Heelproof, Pedestrian Traffic			
Slot Width/Hole Size: 0.125"			
ADA	H-20	FAA	
Yes	No	No	

Please	Item
Check	No.
	6

PS- Perforated Stainless Steel				
Material : Stainless Steel				
DIN Rating: Class A				
Weight: 2.82 # per ft.				
Open Area: 15.25 sq. in. per ft.				
ANSI Rating: Light Duty				
Application: Heelproof, Food/Bev. Process				
Slot Width/Hole Size: 0.125"				
ADA	H-20	FAA		
Yes	No	No		



Please	Item
Check	No.
	7

CG- Cast Iron Slotted				
Material : Cast Iron				
DIN Rating : Class C				
Weight: 5.16 # per ft.				
Open Area: 12.5 sq. in. per ft.				
ANSI Rating: Medium Duty				
Application: Lt. Vehicle Traffic				
Slot Width/Hole Size: 0.375"				
ADA	H-20	FAA		
No	No	No		

Form # FT965

**Date:** 9/5/07

**C.N. No.** 109480

Rev. ORIG

Page 2 of 2