

# M100K

LOAD CLASS  
UP TO C250  
EN-1433 STANDARD

ULMA Linear Drainage Channel type M100K: External width 130 mm; Internal width 100 mm and overall height 80 mm to collect rainwater in 1 metre long units. Integrated galvanized steel\* edges for lateral protection. Locking system consists of 2 screws per metre.

\*Also available with stainless steel edge protection.

MINI



Channel	L (mm)	H (mm)	Width (mm)		Ø Outlet* (mm)		Hydraul. Section (cm <sup>2</sup> )	Pcs. / Pallet
			Z	X	Vert.	Hor.		
M100K	1000	80	130	100	90	-	40	120

\*Vert. outlets on order.



## GRATINGS

Material	Design	Load	Code	L (mm)	Width (mm)	Opening (mm)	Units (x LM)
DUCTILE IRON	SLOTTED	C250	FNX100KCCM	500	123	14	2
	HEELPROOF SLOTTED	C250	FNHX100KCCM	500	123	5	2
GALVANIZED STEEL	PERFORATED	A15	GP100KCA	1000	123	Ø 6	1
	SLOTTED	A15	GN100KCA	1000	123	9	1
	HEELPROOF MESH	B125	GEHX100KCB	1000	123	30 x 10	1
STAINLESS STEEL	SLOTTED	A15	IN100KCA	1000	123	7	1
	PERFORATED	A15	IP100KCA	1000	123	Ø 6	1
	MESH	B125	IX100KCB	1000	123	30 x 20	1
COMPOSITE	MESH	B125	PE100KCBM	500	123	14 x 12,5	2

## LOCKING SYSTEM

SCREW LOCKING SYSTEM. 2 screws per metre.



END CAPS	
Code	Type
T100MKC	CLOSED



**TDS**  
TRENCH DRAIN SYSTEMS  
trenchdrain.com  
610-638-1221

Largest stocking distributor in the US

