


Dimensional Data (Imperial and [Metric]) are subject to manufacturing tolerances and change without notice. Linear (in[mm]), Area (in²[mm²], & Weight (lbs[kg]).

Please	Item	Part	Item
Check	No.	Number	I.D.
✓			
	22	64063	P6-FS

Back to Index



FS GRATE ENGINEERING SPECIFICATION: ZURN P6-FS

40" [1016mm] X 5-3/8" [137mm] Stainless steel fabricated slotted grate weighing 1.7 lbs per linear foot [2.6kg/m]. The grate has an open area of 12.0 in² per linear foot [253cm²/m]. Grate conforms to DIN rating of A, ANSI rating of Light-Duty, ADA compliant* and ASTM A-240 TYPE 304 (316 by request).



FS - Slotted			
Material: Type 304 Stainless Steel			
DIN Rating: Class A			
Weight: 1.7 lbs/ft. [2.6kg/m]			
Open Area: 12.0 in ² /ft. [253cm ² /m]			
ANSI Rating: Light-Duty			
Application: Pedestrian Traffic			
Slot Width/Hole Size: 3/8" [9.5mm]			
ADA: Yes*			
H-20: No			
FAA: No			

^{*} Elongated openings must be placed perpendicular to the dominant direction of travel.

Page 22 of 70

Zurn Industries, LLC | Specification Drainage Operation 1801 Pittsburgh Avenue, Erie, PA U.S.A. 16502 · Ph. 855-663-9876, Fax 814-454-7929 In Canada | Zurn Industries Limited

3544 Nashua Drive, Mississauga, Ontario L4V 1L2 · Ph. 905-405-8272, Fax 905-405-1292

Rev. AL Date: 04/16/15 C.N. No. 132548 Form Number: FT641