

Dimensional Data (Imperial and [Metric]) are subject to manufacturing tolerances and change without notice. Linear (in[mm]), Area (in²[mm²], & Weight (lbs[kg]). Please Part Item Item **Back to Index** Check Number I.D. No. 36 94001 P6-HPP 20 [508] 0 0 0 0 <u></u> 0 0 \prod \prod \Box Ш ПП \mathbb{I} Ш П Ш П Ш O Ш Ш Ш ПТ П 0 0 ⊚ (O) **(1)** 0 0 0

HPP GRATE ENGINEERING SPECIFICATION: ZURN P6-HPP

20" [508mm] X 5-3/8" [137mm] High Density Polyethylene (HDPE) heel-proof slotted grate weighing .9 lbs per linear foot [1.3kg/m]. The grate has an open area of 17.4 in² per linear foot [367cm²/m]. Grate conforms to DIN rating of A, ANSI rating of Light-Duty, ADA compliant*, and Densetec 100 HDPE or Approved Equivalent.

HPP - Heel-Proof Slotted	
Material:	HDPE
DIN Rating:	Class A
Weight: .9	lbs/ft. [1.3kg/m]
Open Area: 1	7.4 in ² /ft. [367cm ² /m]
ANSI Rating:	Light-Duty
Application: Heel-Proof, Pedestrian	
Slot Width/Hole Size: 1/4" [6.4mm]	
ADA:	Yes*
H-20:	No
FAA:	No

^{*} Elongated openings must be placed perpendicular to the dominant direction of travel.

Page 36 of 70

Date: 04/16/15 C.N. No. 132548 Form Number: FT641

ΑL

Rev.