



Review: 2013-06

ULMA Architectural Solutions reserves the right to modify the specifications of any of its products without prior notice.

Information about the shown products is only indicative and is based on the existing technical features at the time of issuing.

In the event of any discrepancy in the translation of this document into different languages, the Spanish version will be used.

Latest version in www.ulmaarchitectural.com

For more details, see technical sheets and installation guide.

Description

ULMA multiV+® Polymer concrete linear drainage sump unit model AR200G.

For self-cleaning optimized V-shaped V+ section channels.

Protective galvanized steel edge with a real thickness of 2+2 mm, smooth, without breakage of the protective zinc layer, avoiding water accumulation and preventing corrosion.

Boltless locking system ULMA Rapidlock®, 8 fixing points per lm.

Load class up to D400, EN 1433 Standard, without reinforcement frame.

Vertically and horizontally aligning tongue and groove joints.

CE Conformity Declaration and compliance with EN 1433 Standard.

Total height 550 mm, internal width 200 mm, total width 236 mm and total length 500 mm.

Ø110 mm, Ø160 mm and Ø200 mm preformed knockouts with triple lipped seals for water tight connection.

CR200 bucket compatible.

ULMA

ARCHITECTURAL SOLUTIONS

**DRAINAGE
SYSTEMS**

Tel.: +34 943 78 06 00

info@ulmaarchitectural.com

ulmaarchitectural.com