



MINI system					
External width : 130mm					
Internal width: 100mm					
Length: 1000mm					
Channel reference	Height (mm)		Hydraulic section (cm ²)	Ø outlet (mm)	
	Total	Internal		Vert.	Hortz.
M100K	80	42	40	90	-

Review: 2013-03

ULMA Architectural Solutions reserves the right to modify the specifications of any of its products without prior notice.

Information about the shown products is only indicative and is based on the existing technical features at the time of issuing.

In the event of any discrepancy in the translation of this document into different languages, the Spanish version will be used.

Latest version in www.ulmaarchitectural.com

For more details, see technical sheets and installation guide.

Description

ULMA polymer concrete linear drainage channel model M100K.

Protective galvanized steel edge with a real thickness of 1+1mm, smooth, without breakage of the protective zinc layer, avoiding water accumulation and preventing corrosion.

Screwed channel base locking system, two fixing points per lm.

Load class up to C250, EN 1433 Standard.

Vertically and horizontally channel aligning tongue and groove joints.

CE Conformity Declaration and compliance with EN 1433 Standard.

External width 130 mm, internal width 100 mm and total length 1000 mm. Total height 80 mm.



ARCHITECTURAL SOLUTIONS



Tel.: +34 943 78 06 00
info@ulmaarchitectural.com
ulmaarchitectural.com