

HydroTec[™] Maxi System

Materials: Fiber-reinforced concrete channels with

ductile iron edge protection

Load Class: C, D, E, F - depending on encasement

Nominal Width: 4", 6" (sloped), 8", 12", 16" (neutral)

Grate Options: Ductile iron grates, various patterns

Application Areas: Industrial areas, airports,

heavy-traffic loading areas

Features: Patented grate-locking system - No Fasteners! Heavy-duty ductile iron edge rails are cast into the channel body.

Integrated lugs prevent longitudinal shifting of the grate.



Materials: Fiber-reinforced concrete channels with

galvanized steel edge protection

Load Class: A, B, C

Nominal Width: 4", 6" (sloped), 8" (neutral)

Grate Options: Galvanized steel slotted/mesh

perforated heel-proof, ductile iron

Application Areas: Commercial driveways, parking lots,

pedestrian/cycle areas

Features: Patented grate-locking system - No Fasteners! Galvanized steel edge rails are cast into the channel body.

HydroTec[™] Mini System

Materials: Fiber-reinforced concrete channels with galvanized steel edge protection

Periori Ton anda biana

Load Class: A, B, C

Nominal Width: 4" (neutral)

Grate Options: Galvanized steel slotted/mesh, ductile iron

Application Areas: Garage and patio areas, residential

driveways/terraces

Features: Bolt-less grate-locking system - No Fasteners!

Easy to install, perfect for smaller DIY projects







HydroBlock[™] System

Materials: Ductile iron

Load Class: Up to Class F - depending on encasement

Nominal Width: 4", 6", 8", 12" (neutral)

Grate Options: Ductile iron (one-piece)

Slotted and ADA patterns

Application Areas: Industrial areas, airports,

heavy-traffic loading areas

Features: Durable, one-piece design is easy to install, low-maintenance, and rattle-free. Can be re-used / re-installed.

Water-tight, anti-torque joints. Small job site footprint.



Materials: Ductile iron, powder-coated aluminum

Load Class: Up to Class F - depending on encasement

Nominal Width: 4.5" (ductile iron), 5" (aluminum)

Grate Options: One-piece, longitudinal slot design

Application Areas: Indoor/covered parking areas,

pedestrian walkways/terraces

Features: Low-profile, one-piece design is easy to install,

easy to clean, low-maintenance, and rattle-free

FastTrack[™] System

Materials: HDPE channels with optional stainless steel edge guards or ductile iron frames

Load Class: A, B, C, D

Nominal Width: 6" (sloped)

Grate Options: HDPE, Polypro, Stainless steel, Galvanized steel, ductile iron - various patterns

Application Areas: Commercial driveways/parking, hospitality, retail/mixed-use, pedestrian/cycle areas

Features: Lightweight channels, solid joint connections,

integral bottom outlet, chemical-resistant







Stainless Steel Systems

Materials: 16-gauge, 14-gauge - 304, 314, 316 stainless steel channels

Load Class: A, B, C

Nominal Width: 4", 6", 8" - sloped or neutral

Grate Options: 304 Stainless steel - slotted, perforated, heavy-duty bar grates, ADA/heel-proof per job requirements

Application Areas: Commercial kitchens, food processing,


breweries, healthcare, laboratories

Features: Superior corrosion resistance - great for high-sanitation

areas. Minimal joints - welded seams and end-caps.

Stainless steel systems are designed and quoted per contractor/job specifications. Full customization available for channel length/width/profile, layouts and channel radius.

For more information, email: Todd.Amerson@SiouxChief.com



Consider Sioux Chief your Total Trench Drain source. We're here to help with your next trench drain project

Support Materials:

- Spec Sheets
- BIM/Revit files
- Job Sketches / Design layouts

Professional Services:

- System selection and optimization
- Hydraulic calculations

Contact: Todd Amerson Todd.Amerson@SiouxChief.com















