

DG0655

POLYCAST 600 SERIES 316L STAINLESS WEDGE WIRE GRATE



PART NO.	MATERIAL	WEIGHT	OPEN AREA	FLOW RATE
DG0655	316L SS	11 LBS.	17%	35.56 GPM PER LINEAR FOOT WITH 1/2" OF HEAD
DG0655H		5.5 LBS.		

**DIN APPLICATION LOAD CLASS B:** SIDEWALKS, PARKING LOTS AND CAR PARKING DECKS  
DESIGNED FOR A DISTRIBUTED PRESSURE OF 28,100 LBS. (125kN)

**MEETS THE FOLLOWING STANDARDS & SPECIFICATION:**

- DIN 19580 / DIN EN 1433 DRAINAGE CHANNELS FOR VEHICULAR AND PEDESTRIAN AREAS.
- THE AMERICANS WITH DISABILITIES ACT OF 1990: 4.5.4.
- ASME A112.6.3. SECTION 7.12 HEEL RESISTANT STRAINERS AND GRATES.
- AUSTRALIAN STANDARD AS 3996-2006 CLAUSE 3.3.6.

SYSTEM MFG	SYSTEM	LOCKING DEVICE
HUBBELL	POLYCAST 500	DA0542S
	POLYCAST 600	DA0642S
TDS	SS0500	SS0542S
	SS0600	SS0642S

