

486


GRATE FRP VINYLESTER 0.88" BAR SPACING CLASS B



PART NO.	MATERIAL	WEIGHT	OPEN AREA	FLOW RATE
486	(FRP) FIBER REINFORCED POLYMER WITH VINYL ESTER RESIN	1.94 LBS.	60%	117.46 (GPM PER LINEAR FOOT WITH 1/2" OF HEAD)
487		4.00 LBS.		

DIN APPLICATION LOAD CLASS B: SIDEWALKS, PARKING LOTS AND CAR PARKING DECKS. DESIGNED FOR A DISTRIBUTED PRESSURE OF 28,100 LBS. (125kN)

MEETS THE FOLLOWING STANDARDS & SPECIFICATION: DIN 19580 / DIN EN 1433 DRAINAGE CHANNELS FOR VEHICULAR AND PEDESTRAIN AREAS.



SYSTEM MFG	SYSTEM	LOCKING DEVICE
ULMA	U100K & U100KX	LD100X-5
	U100K CATCH BASIN	LD100X-5CB
	M100K & M100KX	NONE AVAILABLE
	M100V	NONE AVAILABLE
	HYDROPLUS	LD100X-5
	HYDROPLUS MINI	NONE AVAILABLE
	D100	LD100X-5

GRATE PATTERN OPENINGS

