

DG0620-DG0630

BRONZE AGE CATHEDRAL PATTERN 5.12" WIDE GRATE



PART NO.	MATERIAL	WEIGHT	OPEN AREA	FLOW RATE
DG0620	GALVANIZED	7 LBS.	29%	60.8 GPM PER LINEAR FOOT WITH 1/2" OF HEAD
DG0620H		4 LBS.		
DG0630	304 SS	7 LBS.		
DG0630H		4 LBS.		

DIN APPLICATION LOAD CLASS A: PEDESTIAN, RESIDENTIAL, BICYCLES AND GOLF CARTS
DESIGNED FOR A DISTRIBUTED PRESSURE OF 3,372 LBS. (15kN)

MEETS THE FOLLOWING STANDARDS & SPECIFICATION:

- DIN 19580 / DIN EN 1433 DRAINAGE CHANNELS FOR VEHICULAR AND PEDESTRIAN AREAS.
- THE AMERICANS WITH DISABILITIES ACT OF 1990: 4.5.4.
- ASME A112.6.3. SECTION 7.12 HEEL RESISTANT STRAINERS AND GRATES.

SYSTEM MFG	SYSTEM	LOCKING DEVICE
HUBBELL	POLYCAST 500	DA0542S
	POLYCAST 600	DA0642S
TDS	SS0500	SS0542S
	SS0600	SS0642S

COUNTER-SUNK THRU HOLE FOR
3/8" HARDWARE. (QTY. 2) ON 48"
AND (QTY. 1) ON 24"

