



610-638-1221
sales@trenchdrain.com
PO BOX 377 - FREMONT, OH 43420

PROJECT ID: _____
CONTRACT NO: _____
LOCATION: _____

RELEASED: 1-17-24
REVISION: -

SM-CAULK

AMERIMAX® SeamerMate® 10 OZ CARTRIDGE

MFG.	SYSTEM	CURE TIME
HUBBELL	POLYCAST 500	24 HOURS
	POLYCAST 600	
	POLYCAST 700	
TDS	SS0500	
	SS0600	
	SS1200	
	FP0600	
	FP0800	
	FP1200	

AMERIMAX® SeamerMate® IS A SEMI-SELF LEVELING TRI-POLYMER BASED FORMULA PRIMARILY USED TO SEAL DRAINAGE CONNECTIONS IN NEW INSTALLS OR DAMAGED SYSTEMS. EFFECTIVE WITH METAL, POLYMER CONCRETE, AND POLYMER FIBERGLASS SURFACES.

-(1) 10 OZ TUBE COVERS 25 CHANNEL SEAMS ON AVERAGE WITH A 1/4" BEAD.

-U.V. RESISTANT WITH 4% VOC CONTENT.

California residents see Prop 65 Warnings



DISCLAIMER - The customer and the customer's architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Systems and/or its manufacturers. TRENCH DRAIN SYSTEMS MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.